

# Premium Plus Stucco



## Description

Amerimix Premium Plus Stucco is a preblended mix of portland cement, sand, and advanced proprietary chemical admixtures. It requires only the addition of water to create a consistent, workable stucco mix with excellent adhesion and handling properties, extended board life and resistance to shrinking and cracking.

## Benefits

**Consistency** - Preblended product eliminates jobsite problems of inconsistent mortar batches

**Water resistant**

**Extended mortar board life** means less retempering is required in hot or windy climates

**Reduced shrinking & cracking**

**Outstanding workability**

**Pumpable**

**Superior adhesion**

## Installation

### Mixing:

Pour clean water into mixer. Add dry stucco mix. For maximum performance, mix for a minimum of 5 minutes in a mechanical batch mixer. Add additional water to obtain optimal workability and consistency.

### Retempering:

Retempering Amerimix Premium Plus Stucco is limited to 1.5 hours in the summer and 2.5 hours in the winter after initial batching. Retempering will not adversely affect stucco quality if only evaporated water is replaced.

### Application:

Amerimix Premium Plus Stucco should be applied in accordance with ASTM C926, traditional best practices and local building codes. All surfaces should be dampened before application. Premium Plus Stucco should be applied for all coats of work as a complete system at a minimum thickness of 3/4 inches. Fibers may be added by the manufacturer per customer specification.

### Limitations:

Adding excessive water or excessive retempering may affect finished product. Do not apply if air temperature or substrate surface is below 40° F ( 4° C), or over 100° ( 37°) within 48 hours. Shelf life is approximately 6 months if stored in dry conditions.

## Property Specification Requirements

Plastic (Stucco) Cement	Compressive Strength Minimum psi (MPa)	Water Retention Minimum %	Air Content Maximum %	Water Absorption Relative % (G/100CM2)
Reference Stucco	28 days 1980 (12.5)	70	18	4.2
Amerimix Stucco	28 days 2,951 (15.5)	81	11.82	0.9

## Packaging & Storage

Premium Plus Stucco is available in 3,000 lb. super sacks and 80 lb. bags. Product contains cement and should be covered to protect from weather.

## Certification & Quality Control

AMERIMIX Premium Plus Stucco conforms to ASTM C1328 Standard Specification for Plastic ( Stucco) Cement and ASTM C926 Standard Specification for Application of Portland Based Plaster. Certified Test results are available from the manufacturer. Product mix designs are proprietary information which may be substituted at the discretion of Amerimix. The manufacturer makes no guarantee of finished work. The user is responsible for the following recommended practices.

## Safety Precaution

KEEP OUT OF REACH OF CHILDREN AND ANIMALS. Safety glasses and a dust mask are recommended when handling any stucco containing silica. The materials mixed on site are alkaline on contact with water, irritating to the eyes and skin. In case of eye contact, flush repeatedly with clean water and see a physician immediately. Do not rub eyes!. Wash hands thoroughly after handling and before eating. Do not take internally. Read MSDS prior to use.

## Warranty

LIMITED 1 YEAR WARRANTY FROM DATE OF MANUFACTURE: Bonsal American warrants that this product and the materials used therein meet or exceed the applicable standards listed and enforced at the time of manufacture. Bonsal American will replace any product or part which proves defective due to quality of ingredients used or due to the manufacturing process itself. This Warranty shall apply only if the product is used in strict accordance with applicable specifications and instructions provided by Bonsal American for its use, and Bonsal American shall not be liable otherwise. Replacement of any defective product, or, at Bonsal American's option, refund of the purchase of any defective product shall be the buyer's sole remedy under this Warranty, and Bonsal American shall in no event be liable for any damages in excess of the purchase price of the defective product. BONSAI AMERICAN SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL OR SPECIAL DAMAGES INCLUDING LOSS OF PROFITS OF ANY KIND. Product demonstrations are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. This Warranty constitutes the sole warranty given by Bonsal American in connection with this product. No modification of this Warranty in favor of any buyer shall be valid unless given in writing and signed by an officer of Bonsal American. Bonsal American has authorized no person to make or give any other warranties or representation, oral or written on its behalf. IN PARTICULAR, THERE ARE NO IMPLIED WARRANTIES, INCLUDING WITHOUT EXCEPTION WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

# Customer Support

**AMERIMIX**  
2941 5th Ave. North  
St. Petersburg, FL 33713  
888-313-0755 (nationwide)  
800-851-3231 (Florida only)

[www.amerimix.com](http://www.amerimix.com)  
[support@amerimix.com](mailto:support@amerimix.com)

Amerimix is a division of Bonsal American